

Bestell- Nr.			Max. Radiallast (Rolle)		Max. Axiallast (Rolle)	
	Durch- messer	Breite	Dyna- misch	Sta- tisch	Dyna- misch	Sta- tisch
	[mm]	[mm]	[N]	[N]	[N]	[N]

TPV40	60	33	12200	4900	7560	2650
TPV62	90	44,5	23100	10100	14200	6850
TPV62-1	90	44,5	23100	10100	14200	6850
TPV76	120	50,5	63500	89000	25700	53400
TPV125	165	76	148100	2E+05	58500	1E+05

Bestell- Nr.	Rolle		V-führung		Bolzen		Gewinde		Zentrierbund		Innen- sechskant	Gehäuse- bohrung	Gewicht
	Ø	Breite	Ø	Dicke	Ø	Länge	Länge	Größe	Ø	Länge			
	A	B	F	G	K	L	M	N	R	S			
	±0,4	±0,4	±0,05	±0,26	+0,00/- 0,02	±0,4	±0,4			±0,4			
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]		[mm]	[mm]	[mm]	[mm]	[kg]

TPV26	40	20,0	26	10,0	10	23,0	13,0	M10x1,0	13,1	0,8	4	10,02	0,23
TPV32	50	22,0	32	11,0	12	25,0	14,0	M12x1,5	15,9	0,8	4	12,02	0,26
TPV40	60	33,0	40	17,0	14	40,0	26,0	M14x2,0	18,0	1,6	8	14,02	0,58
TPV62	90	44,5	62	23,0	24	57,9	34,9	M24x3,0	32,0	1,6	8	24,02	1,79
TPV62-1	90	44,5	62	23,0	24	49,5	25,0	M24x1,5	32,0	1,6	8	24,02	1,9
TPV76	120	50,5	76	26,0	30	70,0	40,0	M30x3,5	44,5	1,6	12	30,02	3,27
TPV100	140	50,5	100	26,0	30	80,0	50,0	M30x3,5	44,5	1,6	12	30,02	4,11
PV100-1	140	50,5	100	26,0	30	69,5	40,0	M30x3,5	44,5	1,6	12	30,02	4,05
TPV125	165	76,0	125	37,8	48	105,0	60,0	M48x5,0	82,5	1,6	12	48,02	12,4

